



FACEALL III

Time Attendance & Access Control Machine



Introduction

A new concept of Korean streamline design, 2.8" screen, quickly identify international advanced algorithms, isn't addicted by glasses, twins and hairstyle, USA high-speed stable ATMEL engine CPU, Large capacity of 1500 faces, 5000 fingerprints, 5000 cards, 500,000 records, using high definition double cameras, the latest high-tech ultra-bright double infrared lamps, suitable for different light environment changes, strong management platform, Self-help EXCEL mode, pc attendance software mode, multi-function recognition such as Face+Fingerprint+password+punch card.

Specifications

Camera	Two high definition camera	Infrared Lamp	Ultra-bright lamp four white light
Punch Card Function/Body Induction	Yes	Displayer	Color Screen 2.8" TFT LCD
LED Lights	Two (Red, Green)	Input parts	A WG 26/34 input (can be external card reader module)
Communication Mode	TCP/IP, WIFI	U Disk Interface	Yes (Remarks: only support FAT32 file system)
Voice Output	Yes	Operating System	LINUX VER3.6.5
User/Fingerprint registration Capacity	5000	Face registration Capacity	1500
User record/Management record	500000/10000	Authentication Method	Face, Fingerprint, Card, Password
Access Control Function	Essential Opening door function,Optional control gate / time management / Anti-submarine / Duress alarm function	Attendance Function	Attendance(On/Off duty) Time Quantum
Alarm Function	Yes	Power Management Function	Sleeping Function
U Disk Upload/Download Function Registration Information, Record	Yes	Dynamic Ip Allocation	Yes
Algorithm Version	Face v 4.0	FAR/FRR	0.01% / 1%
Matching Speed	< 1.0 Second	Smart Update Function	Yes
Face Recognition Mode	Support 1:N/1:1	Size	L174*W87*H142MM
Working Voltage	DC 9V - 12V	Working Humidity	20% - 80%
Working Temperature	0°C - 45°C		

Dimensions

