



## HE TS 2000


**Our Pro series tripod turnstiles represent classic and safe way to protect your premises. They are used in various indoor environment applications. They fit perfectly as an economical option in the office buildings and other related applications.**



Access Control System



Fingerprint Recognition



Drop-arm



Bi-directional



Mechanical Unlocking

## Features

- SUS304 stainless steel housing
- Bi-directional tripod turnstile with arm drop function
- LED pictograms for intuitive user experience and high throughput in both directions
- High quality at an affordable price
- Low power consumption
- Wide range of accessories
- Easy and simple installation process
- Easy to maintain and monitor

# Specifications

|                                    |             |   |
|------------------------------------|-------------|---|
| Power requirements                 |             | AC110V/220V, 50/60Hz                            |
| Power consumption                  | Starting    | 73W   |
|                                    | Standby     | 20W   |
|                                    | Unlock      | 63W   |
| Working temperature                |             | -28 °C - 60 °C                                  |
| Working humidity                   |             | 5%-80%  |
| Working environment                |             | Indoor/Outdoor(if sheltered)                    |
| Speed of throughput                | RFID        | Maximum 30/minute                               |
|                                    | Fingerprint | Maximum 25/minute                               |
| Lane width(mm)                     |             | 505   |
| Footprint(mm*mm)                   |             | 785*1110  |
| Dimension(mm)                      |             | L=1110, W=280, H=987                            |
| Dimension with packing(mm)         |             | L=1175, W=370, H=1070                           |
| Net weight(kg)                     |             | 46  |
| Weight with packing(kg)            |             | 54  |
| LED indicator                      |             | Y   |
| Cabinet material                   |             | SUS304 Stainless Steel                          |
| Lid material                       |             | SUS304 Stainless Steel                          |
| Barrier material                   |             | SUS304 Stainless Steel                          |
| Barrier movement                   |             | Rotation  |
| Emergency mode                     |             | Y   |
| Security level                     |             | Medium  |
| Mean cycles between failure (MCBF) |             | 1 million                                       |
| Options/Accessories                |             | Counter, SUS316 Cabinet and Lid, Remote Control |

## Dimensions (mm)

